

サイズ表

カートリッジヒーター

(inch)

カートリッジの直径	シース長 [mm]	電圧 [v]	容量 [w]	コードNo.	カートリッジの直径	シース長 [mm]	電圧 [v]	容量 [w]	コードNo.
1/4" 6.25mm (±0.05)	25.4	120	80	W201Y	1/2" 12.60mm (±0.05)	76.2	240	250	W410I
	31.8	120	75	W202Y		240	300	W412I	
		120	100	W203Y		240	250	W413I	
		120	50	W204Y		240	300	W414I	
	38.1	120	100	W205Y		101.6	120	350	W415I
		120	100	W206Y		240	400	W416I	
	50.8	120	100	W207Y		127.0	240	350	W417I
120		100	W208Y	240		400	W418I		
240		125	W208Y	120		500	W419I		
76.2	120	100	W209Y	240		500	W420I		
	120	100	W210Y	152.4		120	500	W421I	
101.6	120	200	W211Y	240		500	W422I		
	240	200	W212Y	240		750	W423I		
3/8" 9.42mm (±0.05)	38.1	240	150	W3010		165.1	240	1000	W424I
	50.8	120	50	W3020	177.8	120	500	W425I	
		120	100	W3030	240	600	W426I		
		240	150	W3040	203.2	120	500	W427I	
		240	200	W3050	240	1000	W428I		
	57.2	120	75	W3060	228.6	240	500	W429I	
		120	125	W2070	240	1000	W430I		
		120	175	W3080	254.0	240	500	W431I	
		240	250	W3090	240	1000	W432I		
		240	300	W3100	304.8	240	1000	W433I	
	76.2	120	100	W3110	240	1500	W434I		
		120	150	W3120	31.8	120	50	W5010	
		120	200	W3130	50.8	120	200	W5020	
		240	200	W3140	57.2	120	250	W5030	
		240	250	W3150	240	250	W5040		
		240	300	W3160	76.2	240	500	W5050	
		240	400	W3170	101.6	240	500	W5060	
		240	500	W3210	240	600	W5070		
	101.6	240	250	W3180	127.0	240	500	W5080	
		240	300	W3190	240	750	W5090		
		240	400	W3200	152.4	240	500	W510K	
		240	500	W3210	240	750	W511K		
		127.0	240	300	W322S	240	1000	W512K	
		240	500	W323S	177.8	240	1000	W513K	
		152.4	120	400	W324S	240	500	W514K	
			240	400	W325S	240	850	W515K	
		177.8	240	600	W326S	240	1000	W516K	
			240	1000	W328S	240	1500	W517K	
203.2	240	500	W329S	254.0	240	1000	W518K		
	120	600	W330S	240	2000	W519K			
240	240	600	W331S	304.8	240	1000	W520K		
	240	600	W332S	240	1500	W521K			
254.0	240	1000	W333S	76.2	240	500	W601A		
	120	600	W334S	101.6	240	500	W602A		
	240	600	W335S	127.0	240	1000	W603A		
	240	1000	W336S	240	500	W604A			
304.8	240	600	W336S	152.4	240	1000	W605A		
	240	600	W335S	240	500	W606A			
	240	1000	W336S	240	1000	W607A			
	177.8	240	1000	177.8	240	1000	W608A		
	203.2	240	1000	203.2	240	1000	W609A		
	240	2000	W610A	254.0	240	2000	W611A		
1/2" 12.60mm (±0.05)	38.1	120	50	W401H	304.8	240	2000	W612A	
	50.8	240	200	W402H	3/4" 18.95mm (±0.05)	76.2	240	500	W601A
		240	200	W403H		101.6	240	500	W602A
	240	200	W404H	127.0		240	1000	W603A	
	240	250	W405H	152.4		240	500	W604A	
	57.2	240	250	W406H		177.8	240	1000	W605A
63.5	240	250	W407H	203.2		240	1000	W606A	
	240	400	W408H	240		2000	W610A		
76.2	240	125	W409H	254.0		240	2000	W611A	
						304.8	240	2000	W612A

○ 標準型リード長さは250mmです。用途に合せリード長さ、電圧、容量、寸法等変更致します。

各種常備在庫しております